NSN 5306-01-128-8940

Close Tolerance Bolt - Page 1 of 2

Between 0.432 inches and 0.472 inches

Between 4.130 inches and 4.150 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

Spline drive shear head

Head Style:

Head Height:

За



View Online at https://aerobasegroup.com/nsn/5306-01-128-8940

Between 0.247 inches and 0.267 inches
Hole Diameter:
Between 0.065 inches and 0.075 inches
Grip Diameter:
Between 0.4365 inches and 0.4370 inches
Head Minor Diameter:
Between 0.711 inches and 0.717 inches
Thread Diameter:
0.438 inches
Grip Length:
Between 3.678 inches and 3.698 inches
Hole Quantity:
1
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 125000 pounds per square inch
125000 pounds per square inch
125000 pounds per square inch Hole Configuration Style:
125000 pounds per square inch Hole Configuration Style: Spline
125000 pounds per square inch Hole Configuration Style: Spline Material:
125000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp xm-13
125000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp xm-13 Material Specification:
125000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response
125000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment:
125000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate
125000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
125000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
125000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
125000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:

NSN 5306-01-128-8940

Close Tolerance Bolt - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0