NSN 5306-01-128-8940

Close Tolerance Bolt - Page 1 of 2

Between 0.432 inches and 0.472 inches

Between 4.130 inches and 4.150 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

Spline drive shear head

Head Style:

Head Height:

За



View Online at https://aerobasegroup.com/nsn/5306-01-128-8940

| Between 0.247 inches and 0.267 inches |
|--|
| Hole Diameter: |
| Between 0.065 inches and 0.075 inches |
| Grip Diameter: |
| Between 0.4365 inches and 0.4370 inches |
| Head Minor Diameter: |
| Between 0.711 inches and 0.717 inches |
| Thread Diameter: |
| 0.438 inches |
| Grip Length: |
| Between 3.678 inches and 3.698 inches |
| Hole Quantity: |
| 1 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 20 |
| |
| Min. Tensile Strength (psi): |
| Min. Tensile Strength (psi): 125000 pounds per square inch |
| |
| 125000 pounds per square inch |
| 125000 pounds per square inch Hole Configuration Style: |
| 125000 pounds per square inch Hole Configuration Style: Spline |
| 125000 pounds per square inch Hole Configuration Style: Spline Material: |
| 125000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp xm-13 |
| 125000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp xm-13 Material Specification: |
| 125000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response |
| 125000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: |
| 125000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate |
| 125000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: |
| 125000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response |
| 125000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: |
| 125000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: |

NSN 5306-01-128-8940

Close Tolerance Bolt - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0