## NSN 5306-01-129-0566



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-129-0566 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.319 inches and 0.369 inches **Fastener Length:** Between 0.580 inches and 0.610 inches **Head Style:** Dished hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.241 inches and 0.261 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Mil-c-83488 ty2 cl3 military specification single treatment response **Thread Series Designator:** 

Unit Of Measure:

Demilitarization:

No

Unjf

N/a

Shelf Life:

## NSN 5306-01-129-0566

Shear Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.