NSN 5306-01-129-4438

Ribbed Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-129-4438 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.885 inches **Fastener Length:** 1.312 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.615 inches and 0.625 inches **Head Height:** Between 0.185 inches and 0.187 inches **Shoulder Diameter:** 0.360 inches first shoulder and 0.388 inches first shoulder **Shoulder Length:** 0.905 inches first shoulder **Rib Major Diameter:** 0.405 inches Rib Length: 0.407 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.063 inches **Rib Minor Diameter:** 0.062 inches **Rib Quantity:** 12 **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 110000 pounds per square inch **Rib Included Angle:** 90.0 degrees **Shoulder Shape:** Ribbed first shoulder Material:

Steel **Material Specification:**

Astm-a490 assn standard single material response

NSN 5306-01-129-4438

Ribbed Shoulder Bolt - Page 2 of 2

A003b0



Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq416, type 2, calss 1 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg: