NSN 5306-01-130-6095

Machine Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-130-6095

Thread Class:3aThread Direction:Right-handThread Length:0.640 inchesFastener Length:1.203 inchesHead Style:HexagonHead Height:Between 0.203 inches and 0.235 inchesWidth Between Flats:Between 0.553 inches and 0.565 inchesHole Diameter:Between 0.070 inches and 0.080 inchesThread Diameter:0.375 inchesGrip Length:0.188 inchesHole Quantity:3Hole Type:DrilledThready Qty Per Inch (tpi):24Hole Configuration Style:Hexagon flatsSpecial Features:Altered from anch118Material:
Thread Direction:Right-handThread Length:0.640 inchesFastener Length:1.203 inchesHead Style:Head Style:HexagonHead Height:Between 0.203 inches and 0.235 inchesWidth Between Flats:Between 0.553 inches and 0.565 inchesHole Diameter:0.375 inchesGrip Length:0.188 inchesHole Quantity:3Hole Type:DrilledThready Qty Per Inch (tpi):24Hose Configuration Style:Hexagon flatsSpecial Features:Altered from anch118
Right-handRight-handThread Length:0.640 inchesFastener Length:1.203 inchesHead Style:Head Style:HexagonHead Height:Between 0.203 inches and 0.235 inchesWidth Between Flats:Between 0.553 inches and 0.565 inchesHole Diameter:Between 0.070 inches and 0.080 inchesThread Diameter:0.375 inchesGrip Length:0.188 inchesHole Quantity:3Hole Type:DrilledThready Qty Per Inch (tpi):24Hole Configuration Style:Hexagon flatsSpecial Features:Altered from anch118
Thread Length:0.640 inchesFastener Length:1.203 inchesHead Style:Head Style:HexagonHead Height:Between 0.203 inches and 0.235 inchesWidth Between Flats:Between 0.553 inches and 0.565 inchesHole Diameter:Between 0.070 inches and 0.080 inchesThread Diameter:0.375 inchesGrip Length:0.188 inchesHole Quantity:3Hole Type:DrilledThready Qty Per Inch (tpi):24Hole Configuration Style:Hexagon flatsSpecial Features:Altered from anch118
0.640 inches Fastener Length: 1.203 inches Head Style: Hexagon Head Height: Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.553 inches and 0.565 inches Hole Diameter: Between 0.070 inches and 0.080 inches Thread Diameter: 0.375 inches Grip Length: 0.375 inches Hole Quantity: 3 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Hole Configuration Style: Hexagon flats Special Features: Altered from anch118
Fastener Length:1.203 inchesHead Style:HexagonHead Height:Between 0.203 inches and 0.235 inchesWidth Between Flats:Between 0.553 inches and 0.565 inchesHole Diameter:Between 0.070 inches and 0.080 inchesThread Diameter:0.375 inchesGrip Length:0.188 inchesHole Quantity:3Hole Type:DrilledThready Qty Per Inch (tpi):24Hos Onfiguration Style:Hexagon flatsSpecial Features:Altered from anch118
1.203 inchesHead Style:HexagonHead Height:Between 0.203 inches and 0.235 inchesWidth Between Flats:Between 0.553 inches and 0.565 inchesHole Diameter:Between 0.070 inches and 0.080 inchesThread Diameter:0.375 inchesGrip Length:0.188 inchesHole Quantity:3Hole Type:DrilledThready Qty Per Inch (tpi):24Hole Configuration Style:Hexagon flatsSpecial Features:Altered from anch118
Head Style:HexagonHead Height:Between 0.203 inches and 0.235 inchesWidth Between Flats:Between 0.553 inches and 0.565 inchesHole Diameter:Between 0.070 inches and 0.080 inchesThread Diameter:0.375 inchesGrip Length:0.188 inchesHole Quantity:3Hole Type:DrilledThready Qty Per Inch (tpi):24Hole Configuration Style:Hexagon flatsSpecial Features:Altered from anch118
Hexagon Head Height: Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.553 inches and 0.565 inches Hole Diameter: Between 0.070 inches and 0.080 inches Thread Diameter: 0.375 inches Grip Length: 0.188 inches Hole Quantity: 3 Hole Quantity: 24 Hole Configuration Style: Hexagon flats Special Features: Altered from anch118
Head Height:Between 0.203 inches and 0.235 inchesWidth Between Flats:Between 0.553 inches and 0.565 inchesHole Diameter:Between 0.070 inches and 0.080 inchesThread Diameter:0.375 inchesGrip Length:0.188 inchesHole Quantity:3Hole Type:DrilledThready Qty Per Inch (tpi):24Hole Configuration Style:Hexagon flatsSpecial Features:Altered from anch118
Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.553 inches and 0.565 inches Hole Diameter: Between 0.070 inches and 0.080 inches Thread Diameter: 0.375 inches Grip Length: 0.188 inches Hole Quantity: 3 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Hole Configuration Style: Hexagon flats Special Features: Altered from anch118
Width Between Flats: Between 0.553 inches and 0.565 inches Hole Diameter: Between 0.070 inches and 0.080 inches Thread Diameter: 0.375 inches Grip Length: 0.188 inches Hole Quantity: 3 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Hole Configuration Style: Hexagon flats Special Features: Altered from anch118
Between 0.553 inches and 0.565 inches Hole Diameter: Between 0.070 inches and 0.080 inches Thread Diameter: 0.375 inches Grip Length: 0.188 inches Hole Quantity: 3 Hole Quantity: 3 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Hole Configuration Style: Hexagon flats Special Features: Altered from anch118
 Hole Diameter: Between 0.070 inches and 0.080 inches Thread Diameter: 0.375 inches Grip Length: 0.188 inches Hole Quantity: 3 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Hole Configuration Style: Hexagon flats Special Features: Altered from anch118
Between 0.070 inches and 0.080 inches Thread Diameter: 0.375 inches Grip Length: 0.188 inches Hole Quantity: 3 Hole Quantity: 3 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Hole Configuration Style: Hexagon flats Special Features: Altered from anch118
Thread Diameter: 0.375 inches Grip Length: 0.188 inches Hole Quantity: 3 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Hole Configuration Style: Hexagon flats Special Features: Altered from anch118
0.375 inches Grip Length: 0.188 inches Hole Quantity: 3 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Hole Configuration Style: Hexagon flats Special Features: Altered from anch118
Grip Length: 0.188 inches Hole Quantity: 3 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Hole Configuration Style: Hexagon flats Special Features: Altered from anch118
0.188 inches Hole Quantity: 3 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Hole Configuration Style: Hexagon flats Special Features: Altered from anch118
Hole Quantity: 3 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Hole Configuration Style: Hexagon flats Special Features: Altered from anch118
3 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Hole Configuration Style: Hexagon flats Special Features: Altered from anch118
Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Hole Configuration Style: Hexagon flats Special Features: Altered from anch118
Drilled Thready Qty Per Inch (tpi): 24 Hole Configuration Style: Hexagon flats Special Features: Altered from anch118
Thready Qty Per Inch (tpi): 24 Hole Configuration Style: Hexagon flats Special Features: Altered from anch118
24 Hole Configuration Style: Hexagon flats Special Features: Altered from anch118
Hole Configuration Style: Hexagon flats Special Features: Altered from anch118
Hexagon flats Special Features: Altered from anch118
Special Features: Altered from anch118
Altered from anch118
Material
ווומנקו ומו.
Stainless steel
Thread Series Designator:
Unf
Shelf Life:
Shelf Life: N/a
N/a
N/a Unit Of Measure:
N/a Unit Of Measure:
N/a Unit Of Measure: Demilitarization: