

View Online at <https://aerobasegroup.com/nsn/5306-01-130-8983>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.400 inches and 0.450 inches

Fastener Length:

Between 1.410 inches and 1.440 inches

Head Style:

Dished hexagon

Head Height:

Between 0.156 inches and 0.171 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Shoulder Diameter:

0.3115 inches first shoulder and 0.3112 inches first shoulder

Shoulder Length:

0.990 inches first shoulder and 1.010 inches first shoulder

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.222 inches first hole and 1.262 inches first hole

Shoulder Shape:

Round first shoulder

Special Features:

Dry film lubed shank per mcair ps18021 class 15 designated by letter m in part number

Material:

Iron alloy 660

Material Specification:

Ams5732 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0