

View Online at <https://aerobasegroup.com/nsn/5306-01-131-2180>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.568 inches and 0.618 inches

Fastener Length:

Between 1.016 inches and 1.046 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.309 inches and 0.329 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Extended Washer Diameter:

Between 0.575 inches and 0.585 inches

Extended Washer Thickness:

Between 0.040 inches and 0.060 inches

Grip Diameter:

Between 0.3110 inches and 0.3120 inches

Thread Diameter:

0.312 inches

Grip Length:

Between 0.428 inches and 0.448 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Surface Finish:

32.0 microinches grip

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium or cadmium and chromate

Surface Treatment Specification:

Nas 672 assn standard 1st treatment response or mil-c-8837 type 2 class 2 military specification 2nd treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.