

View Online at <https://aerobasegroup.com/nsn/5306-01-131-2904>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.313 inches and 0.363 inches

Fastener Length:

Between 0.948 inches and 0.978 inches

Head Style:

Hexagon

Head Height:

Between 0.110 inches and 0.125 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Washer Quantity:

1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Primary Washer Outside Diameter:

Between 0.433 inches and 0.458 inches

Primary Washer Style:

Flat

Primary Washer Material Thickness:

Between 0.028 inches and 0.036 inches

Material:

Titanium alloy fastener

Material Specification:

Qq-a-250/5, t3 or t4 federal specification single material response primary washer

Surface Treatment:

Anodize primary washer or chromate primary washer

Surface Treatment Specification:

Mil-c-5541 military specification 2nd treatment response primary washer

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-5541 spec.