

View Online at <https://aerobasegroup.com/nsn/5306-01-131-2904>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.313 inches and 0.363 inches

**Fastener Length:**

Between 0.948 inches and 0.978 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.110 inches and 0.125 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Washer Quantity:**

1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Primary Washer Outside Diameter:**

Between 0.433 inches and 0.458 inches

**Primary Washer Style:**

Flat

**Primary Washer Material Thickness:**

Between 0.028 inches and 0.036 inches

**Material:**

Titanium alloy fastener

**Material Specification:**

Qq-a-250/5, t3 or t4 federal specification single material response primary washer

**Surface Treatment:**

Anodize primary washer or chromate primary washer

**Surface Treatment Specification:**

Mil-c-5541 military specification 2nd treatment response primary washer

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-5541 spec.