
# NSN 5306-01-131-2904

Assembled Washer Bolt - Page 1 of 2





## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.313 inches and 0.363 inches

#### Fastener Length:

Between 0.948 inches and 0.978 inches

#### Head Style:

Hexagon

Head Height:

Between 0.110 inches and 0.125 inches

#### Width Between Flats:

Between 0.367 inches and 0.376 inches

### Washer Quantity:

1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

## Primary Washer Outside Diameter:

Between 0.433 inches and 0.458 inches

#### **Primary Washer Style:**

Flat

#### **Primary Washer Material Thickness:**

Between 0.028 inches and 0.036 inches

#### Material:

Titanium alloy fastener

#### **Material Specification:**

Qq-a-250/5, t3 or t4 federal specification single material response primary washer

#### Surface Treatment:

Anodize primary washer or chromate primary washer

### Surface Treatment Specification:

Mil-c-5541 military specification 2nd treatment response primary washer

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

# Unit Of Measure:

--

# NSN 5306-01-131-2904

Assembled Washer Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-5541 spec.