NSN 5306-01-131-2908

Assembled Washer Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-131-2908 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.313 inches and 0.363 inches **Fastener Length:** Between 0.511 inches and 0.541 inches **Head Style:** Hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches Washer Quantity: **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Primary Washer Outside Diameter:** Between 0.433 inches and 0.458 inches **Primary Washer Style:** Flat **Primary Washer Material Thickness:** Between 0.028 inches and 0.036 inches Material: Titanium alloy fastener **Material Specification:** Qq-a-250/5, t3 or t4 federal specification single material response primary washer **Surface Treatment:** Anodize primary washer or chromate primary washer **Surface Treatment Specification:** Mil-c-5541 military specification 2nd treatment response primary washer **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5306-01-131-2908

Assembled Washer Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-5541 spec.