NSN 5306-01-131-5479

Shear Bolt - Page 1 of 2



Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.400 inches and 0.450 inches
Fastener Length:
Between 3.910 inches and 3.940 inches
Head Style:
Dished hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.429 inches and 0.439 inches
Grip Diameter:
Between 0.2490 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 3.490 inches and 3.510 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
160000 pounds per square inch Surface Finish:
Surface Finish:
Surface Finish: 32.0 microinches threads
Surface Finish: 32.0 microinches threads Material:
Surface Finish: 32.0 microinches threads Material: Iron alloy 660
Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification:
Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment:
Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate
Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf
Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data:
Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6704 professional/industrial association standard

NSN 5306-01-131-5479

Shear Bolt - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A003b0