## NSN 5306-01-131-6725

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-131-6725



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.444 inches and 0.494 inches Fastener Length: Between 1.016 inches and 1.046 inches **Head Style:** Dished hexagon **Head Height:** Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches Hole Diameter: Between 0.070 inches and 0.080 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Thread Diameter:** 0.312 inches Grip Length: Between 0.552 inches and 0.572 inches **Hole Quantity:** 3 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hole Configuration Style: Hexagon corners Surface Finish: 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

## NSN 5306-01-131-6725

Shear Bolt - Page 2 of 2



Thread Series Designator:

Unjf

Specification Data:

80205-nas6705 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0