

View Online at <https://aerobasegroup.com/nsn/5306-01-131-8165>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.267 inches and 0.334 inches

Fastener Length:

Between 0.777 inches and 0.824 inches

Head Style:

Double hexagon

Head Height:

Between 0.154 inches and 0.174 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Grip Diameter:

Between 0.2483 inches and 0.2492 inches

Thread Diameter:

0.250 inches

Grip Length:

Between 0.490 inches and 0.510 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Surface Finish:

32.0 microinches grip

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium or cadmium and chromate

Surface Treatment Specification:

Nas 672 assn standard 1st treatment response or mil-c-8837 type 2 class 2 military specification 2nd treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.