## NSN 5306-01-132-0509

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-132-0509 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.518 inches and 0.568 inches **Fastener Length:** Between 3.028 inches and 3.058 inches **Head Style:** Hexagon **Head Height:** Between 0.312 inches and 0.327 inches Width Between Flats: Between 0.928 inches and 0.940 inches **Grip Diameter:** Between 0.6235 inches and 0.6240 inches **Shank Unthreaded Hole Diameter:** 0.141 inches first hole and 0.151 inches first hole **Thread Diameter:** 0.625 inches **Grip Length:** Between 2.490 inches and 2.510 inches Thready Qty Per Inch (tpi): Distance From Head Largest Bearing Surface To Shank Hole Center: 2.894 inches first hole and 2.944 inches first hole **Surface Finish:** 63.0 microinches grip Material: Titanium alloy **Material Specification:** Nas621 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1262 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5306-01-132-0509

Close Tolerance Bolt - Page 2 of 2



Fiig:

A003b0