NSN 5306-01-132-1034

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-132-1034 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.622 inches and 0.692 inches **Fastener Length:** Between 2.673 inches and 2.703 inches **Head Style:** Spline extended washer **Head Height:** Between 0.273 inches and 0.293 inches **Extended Washer Diameter:** Between 0.691 inches and 0.701 inches **Extended Washer Thickness:** Between 0.044 inches and 0.064 inches **Shoulder Diameter:** 0.3740 inches first shoulder and 0.3745 inches first shoulder **Shoulder Length:** 1.928 inches first shoulder and 1.948 inches first shoulder **Head Minor Diameter:** Between 0.904 inches and 0.912 inches **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 **Shoulder Shape:** Round first shoulder **Special Features:** Twenty six degree angle between the threads and the shoulder 0.083 to 0.103 inches long Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

NSN 5306-01-132-1034 Shoulder Bolt - Page 2 of 2



			ıre:

Demilitarization:

No

Fiig:

A003b0