

View Online at <https://aerobasegroup.com/nsn/5306-01-132-1053>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.634 inches and 0.684 inches

**Fastener Length:**

Between 2.894 inches and 2.924 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.263 inches and 0.303 inches

**Extended Washer Diameter:**

Between 0.691 inches and 0.701 inches

**Extended Washer Thickness:**

Between 0.044 inches and 0.064 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Head Minor Diameter:**

Between 0.423 inches and 0.438 inches

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 2.240 inches and 2.260 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Surface Finish:**

32.0 microinches grip

**Material:**

Steel comp h11

**Material Specification:**

Ams6487 assn standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Mil-c-8837, ty2, cl2 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.