

View Online at <https://aerobasegroup.com/nsn/5306-01-132-4786>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.680 inches and 0.730 inches

Fastener Length:

Between 1.690 inches and 1.720 inches

Head Style:

Spline extended washer

Head Height:

Between 0.310 inches and 0.350 inches

Width Between Flats:

Between 0.514 inches and 0.605 inches

Extended Washer Diameter:

Between 0.807 inches and 0.817 inches

Extended Washer Thickness:

Between 0.053 inches and 0.073 inches

Hole Diameter:

Between 0.050 inches and 0.060 inches

Grip Diameter:

Between 0.4360 inches and 0.4370 inches

Thread Diameter:

0.438 inches

Grip Length:

Between 0.990 inches and 1.010 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Hole Configuration Style:

Spline

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Aluminum and chromate

Surface Treatment Specification:

Mil-c-83488, type 2 class 3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.