## NSN 5306-01-132-5282

Shear Bolt - Page 1 of 2

Between 0.535 inches and 0.585 inches

Between 1.295 inches and 1.325 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5306-01-132-5282

Head Style:
Double hexagon w/hole
Head Height:
Between 0.378 inches and 0.398 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Extended Washer Diameter:
Between 0.639 inches and 0.649 inches
Extended Washer Thickness:
0.091 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 0.740 inches and 0.760 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Surface Finish:
32.0 microinches grip
Product Name:
Navy special project
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium or cadmium and chromate
Surface Treatment Specification:
Nas 672 assn standard 1st treatment response or mil-c-8837 type 2 class 2 military specification 2nd treatment response

## NSN 5306-01-132-5282

Shear Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Mil-std (military Standard):

Mil-c-8837 spec.