

View Online at <https://aerobasegroup.com/nsn/5306-01-132-8525>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.677 inches and 0.913 inches

Fastener Length:

Between 4.013 inches and 4.033 inches

Head Style:

Hexagon

Head Height:

Between 0.376 inches and 0.391 inches

Width Between Flats:

Between 1.052 inches and 1.064 inches

Grip Diameter:

Between 0.7482 inches and 0.7491 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Thread Diameter:

0.750 inches

Grip Length:

Between 3.000 inches and 3.016 inches

Thready Qty Per Inch (tpi):

16

Hardness Rating:

36.0 rockwell c and 41.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.856 inches first hole and 3.886 inches first hole

Surface Finish:

63.0 microinches grip

Special Features:

Detent ring in shank

Material Specification:

Ams5643 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0