NSN 5306-01-133-0169

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-133-0169
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.443 inches and 0.510 inches
Fastener Length:
Between 2.203 inches and 2.250 inches
Head Style:
Hexagon
Head Height:
Between 0.234 inches and 0.266 inches
Width Between Flats:
Between 0.240 inches and 0.260 inches
Grip Diameter:
Between 0.4982 inches and 0.4991 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 1.740 inches and 1.760 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
32.0 microinches grip
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Surface Treatment:
Cadmium head and chromate head
Cadmium head and chromate head Surface Treatment Specification:
Surface Treatment Specification:
Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response threads
Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response threads Thread Series Designator:
Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response threads Thread Series Designator: Unjf
Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response threads Thread Series Designator: Unjf Specification Data:
Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response threads Thread Series Designator: Unjf Specification Data: 80205-nas464 professional/industrial association standard
Surface Treatment Specification: Qq-p-416, type 2, cl 2 federal specification single treatment response threads Thread Series Designator: Unjf Specification Data: 80205-nas464 professional/industrial association standard Shelf Life:

NSN 5306-01-133-0169

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0