

View Online at <https://aerobasegroup.com/nsn/5306-01-133-1066>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.291 inches and 0.341 inches

Fastener Length:

Between 3.676 inches and 3.706 inches

Head Style:

Hexagon

Head Height:

Between 0.125 inches and 0.140 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Grip Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Thread Diameter:

0.250 inches

Grip Length:

Between 3.365 inches and 3.385 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.548 inches first hole and 3.598 inches first hole

Surface Finish:

63.0 microinches grip

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4967 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

80205-nas654 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0