

View Online at <https://aerobasegroup.com/nsn/5306-01-133-1564>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.461 inches and 0.553 inches

**Fastener Length:**

Between 0.609 inches and 0.641 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.303 inches and 0.312 inches

**Head Height:**

Between 0.185 inches and 0.190 inches

**First Diameter From Head:**

Between 0.164 inches and 0.174 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.088 inches and 0.148 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.190 inches

**Width Across Flats:**

Between 0.156 inches and 0.159 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

170000 pounds per square inch

**Hardness Rating:**

38.0 rockwell c and 43.0 rockwell c

**Externally Relieved Body Diameter Quantity:**

1

**Surface Finish:**

63.0 microinches grip

**Material:**

Steel comp 410

**Material Specification:**

Ams 5612 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0