

View Online at <https://aerobasegroup.com/nsn/5306-01-133-3867>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.284 inches and 0.351 inches

Fastener Length:

Between 0.669 inches and 0.716 inches

Head Style:

Double hexagon

Head Height:

Between 0.130 inches and 0.150 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Grip Diameter:

Between 0.1885 inches and 0.1894 inches

Shank Unthreaded Hole Diameter:

0.065 inches first hole and 0.075 inches first hole

Thread Diameter:

0.190 inches

Grip Length:

Between 0.365 inches and 0.385 inches

Thread Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.506 inches first hole and 0.538 inches first hole

Surface Finish:

32.0 microinches grip

Material:

Steel comp h11

Material Specification:

Ams6487 assn standard single material response

Surface Treatment:

Cadmium or cadmium and chromate

Surface Treatment Specification:

Nas672 assn standard 1st treatment response or mil-c-8837 type 2, cl 2 military specification 2nd treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.