

View Online at <https://aerobasegroup.com/nsn/5306-01-133-3877>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.344 inches and 0.395 inches

**Fastener Length:**

Between 6.240 inches and 6.260 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.126 inches and 0.141 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Grip Diameter:**

Between 0.2487 inches and 0.2492 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 5.750 inches and 5.766 inches

**Thready Qty Per Inch (tpi):**

28

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

6.171 inches first hole

**Surface Finish:**

63.0 microinches grip

**Special Features:**

Retaining element in shank

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0