## NSN 5306-01-133-4454

Machine Bolt - Page 1 of 2

Between 3.330 inches and 3.407 inches

Between 3.390 inches and 3.437 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5306-01-133-4454

Hexagon Head Height: Between 0.318 inches and 0.338 inches Width Between Flats: Between 0.615 inches and 0.627 inches Hole Diameter: Between 0.070 inches and 0.080 inches Thread Diameter: 0.438 inches Hole Quantity: 3 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Hexagon corners Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment Specification: Qq-p-35 federal specification: Intread Series Designator: Unif
Between 0.318 inches and 0.338 inches  Width Between Flats:  Between 0.615 inches and 0.627 inches  Hole Diameter:  Between 0.070 inches and 0.080 inches  Thread Diameter:  0.438 inches  Hole Quantity:  3  Hole Type:  Drilled  Features Provided: Finished head  Thready Qty Per Inch (tpi):  20  Min. Tensile Strength (psi):  160000 pounds per square inch  Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Hole Configuration Style:  Hexagon corners  Material: Iron alloy 660  Material Specification:  Ams 5737 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment Specification single treatment response  Thread Scries Designator:
Width Between Flats: Between 0.615 inches and 0.627 inches Hole Diameter: Between 0.070 inches and 0.080 inches Thread Diameter: 0.438 inches Hole Quantity: 3 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Hexagon corners Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification single treatment response Thread Scries Designator:
Between 0.615 inches and 0.627 inches  Hole Diameter:  Between 0.070 inches and 0.080 inches  Thread Diameter: 0.438 inches  Hole Quantity: 3  Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 20  Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Hexagon corners  Material: Iron alloy 660  Material Specification: Ams 5737 assn standard single material response  Surface Treatment: Passivate  Surface Treatment Specification single treatment response Thread Series Designator:
Hole Diameter: Between 0.070 inches and 0.080 inches Thread Diameter: 0.438 inches Hole Quantity: 3 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Hexagon corners Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Q-p-35 federal specification single treatment response Thread Series Designator:
Between 0.070 inches and 0.080 inches  Thread Diameter: 0.438 inches  Hole Quantity: 3  Hole Type:  Drilled  Features Provided: Finished head  Thready Qty Per Inch (tpi): 20  Min. Tensile Strength (psi): 160000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Hexagon corners  Material: Iron alloy 660  Material Specification: Ams 5737 assn standard single material response  Surface Treatment: Passivate  Surface Treatment Specification: Q-p-35 federal specification single treatment response Thread Series Designator:
Thread Diameter:  0.438 inches  Hole Quantity: 3  Hole Type:  Drilled  Features Provided:  Finished head  Thready Qty Per Inch (tpi): 20  Min. Tensile Strength (psi): 160000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Hole Configuration Style:  Hexagon corners  Material: Iron alloy 660  Material Specification: Ams 5737 assn standard single material response  Surface Treatment: Passivate  Surface Treatment Specification: Q-p-35 federal specification single treatment response Thread Series Designator:
0.438 inches Hole Quantity: 3 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Hexagon corners Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
Hole Quantity: 3 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Hexagon corners Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
Hole Type:  Drilled  Features Provided: Finished head  Thready Qty Per Inch (tpi): 20  Min. Tensile Strength (psi): 160000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Hole Configuration Style: Hexagon corners  Material: Iron alloy 660  Material Specification: Ams 5737 assn standard single material response  Surface Treatment: Passivate  Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Hexagon corners Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Hexagon corners Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Hexagon corners Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
Finished head  Thready Qty Per Inch (tpi): 20  Min. Tensile Strength (psi): 160000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Hole Configuration Style: Hexagon corners  Material: Iron alloy 660  Material Specification: Ams 5737 assn standard single material response  Surface Treatment: Passivate  Surface Treatment Specification: Qq-p-35 federal specification single treatment response  Thread Series Designator:
Thready Qty Per Inch (tpi): 20  Min. Tensile Strength (psi): 160000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Hexagon corners  Material: Iron alloy 660  Material Specification: Ams 5737 assn standard single material response  Surface Treatment: Passivate  Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Hexagon corners Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Hexagon corners Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
160000 pounds per square inch  Hardness Rating: 36.0 rockwell c and 40.0 rockwell c  Hole Configuration Style: Hexagon corners  Material: Iron alloy 660  Material Specification: Ams 5737 assn standard single material response  Surface Treatment: Passivate  Surface Treatment Specification: Qq-p-35 federal specification single treatment response  Thread Series Designator:
Hardness Rating:  36.0 rockwell c and 40.0 rockwell c  Hole Configuration Style:  Hexagon corners  Material:  Iron alloy 660  Material Specification:  Ams 5737 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:
36.0 rockwell c and 40.0 rockwell c  Hole Configuration Style:  Hexagon corners  Material:  Iron alloy 660  Material Specification:  Ams 5737 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:
Hole Configuration Style: Hexagon corners  Material: Iron alloy 660  Material Specification: Ams 5737 assn standard single material response  Surface Treatment: Passivate  Surface Treatment Specification: Qq-p-35 federal specification single treatment response  Thread Series Designator:
Hexagon corners  Material: Iron alloy 660  Material Specification: Ams 5737 assn standard single material response  Surface Treatment: Passivate  Surface Treatment Specification: Qq-p-35 federal specification single treatment response  Thread Series Designator:
Material: Iron alloy 660  Material Specification: Ams 5737 assn standard single material response  Surface Treatment: Passivate  Surface Treatment Specification: Qq-p-35 federal specification single treatment response  Thread Series Designator:
Iron alloy 660  Material Specification:  Ams 5737 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:
Material Specification:  Ams 5737 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:
Ams 5737 assn standard single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:
Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:
Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:
Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:
Qq-p-35 federal specification single treatment response  Thread Series Designator:
Thread Series Designator:
Unjf

## NSN 5306-01-133-4454

Machine Bolt - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

80205-nas567 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0