NSN 5306-01-133-5816

Shear Bolt - Page 1 of 2

Between 1.000 inches and 1.050 inches

Between 3.885 inches and 3.915 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

Head Style:

За



View Online at https://aerobasegroup.com/nsn/5306-01-133-5816

Spline extended washer
Head Height:
Between 0.373 inches and 0.413 inches
Extended Washer Diameter:
Between 0.928 inches and 0.938 inches
Extended Washer Thickness:
Between 0.102 inches and 0.122 inches
Grip Diameter:
Between 0.5605 inches and 0.5615 inches
Head Minor Diameter:
Between 0.711 inches and 0.717 inches
End Application:
Spec item
Thread Diameter:
0.562 inches
Grip Length:
Between 2.865 inches and 2.885 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Surface Finish:
32.0 microinches grip
Material:
Steel comp h11
Material Specification:
Ams6487 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Mil-c-8837, type 2 class 2 military specification single treatment response

NSN 5306-01-133-5816

Shear Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-c-8837 spec.