

View Online at <https://aerobasegroup.com/nsn/5306-01-133-8596>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.470 inches and 0.500 inches

**Fastener Length:**

2.780 inches

**Head Style:**

Hexagon

**Head Height:**

0.200 inches

**Width Between Flats:**

Between 0.740 inches and 0.752 inches

**Shoulder Diameter:**

0.4975 inches first shoulder and 0.4985 inches first shoulder

**Shoulder Length:**

2.190 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.108 inches first hole and 0.113 inches first hole

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

201000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.450 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Paint head

**Surface Treatment Specification:**

Qq-c-320 federal specification single treatment response grip

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.