NSN 5306-01-133-8608

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-133-8608

View Online at https://aerobasegroup.com/nsn/5306-01-133-8608
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.429 inches and 0.479 inches
Fastener Length:
Between 2.127 inches and 2.157 inches
Head Style:
Dished hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.554 inches and 0.564 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 1.678 inches and 1.698 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5737 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
On a 440 time 2 class 2 federal an elification single treatment recovers
Qq-p-416, type 2 class 2 federal specification single treatment response
Thread Series Designator:
Thread Series Designator:
Thread Series Designator: Unjf
Thread Series Designator: Unjf Specification Data:
Thread Series Designator: Unjf Specification Data: 80205-nas6306 professional/industrial association standard
Thread Series Designator: Unjf Specification Data: 80205-nas6306 professional/industrial association standard Shelf Life:

--

NSN 5306-01-133-8608

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0