

View Online at <https://aerobasegroup.com/nsn/5306-01-133-8609>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.594 inches and 0.644 inches

**Fastener Length:**

Between 7.354 inches and 7.384 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.378 inches and 0.398 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Extended Washer Diameter:**

Between 0.639 inches and 0.649 inches

**Extended Washer Thickness:**

Between 0.081 inches and 0.101 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 6.740 inches and 6.760 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas 672 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas626 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0