## NSN 5306-01-134-1966

Assembled Washer Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-134-1966 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.761 inches and 0.875 inches **Fastener Length:** Between 0.844 inches and 0.875 inches **Head Style:** Hexagon **Head Height:** Between 0.270 inches and 0.295 inches Width Between Flats: Between 0.551 inches and 0.562 inches Washer Quantity: **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 **Hardness Rating:** 40.0 rockwell c primary washer and 50.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.640 inches and 0.654 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** 0.035 inches Material: Steel comp 1050 or steel comp 1566 **Material Specification:** Sae assn standard all material responses primary washer **Surface Treatment:** Cadmium fastener or zinc fastener **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5306-01-134-1966

Assembled Washer Bolt - Page 2 of 2



Fiig:

A003b0