

View Online at <https://aerobasegroup.com/nsn/5306-01-134-2715>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.535 inches and 0.585 inches

Fastener Length:

Between 1.732 inches and 1.762 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.378 inches and 0.398 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Extended Washer Diameter:

Between 0.639 inches and 0.649 inches

Extended Washer Thickness:

0.091 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

End Application:

Aircraft, f-111 (fms only); aircraft, tomcat f-14

Thread Diameter:

0.375 inches

Grip Length:

Between 1.177 inches and 1.197 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Surface Finish:

32.0 microinches grip

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium or cadmium and chromate

Surface Treatment Specification:

Nas 672 assn standard 1st treatment response or mil-c-8837 type 2 class 2 military specification 2nd treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.