## NSN 5306-01-134-5706

Machine Bolt - Page 1 of 2

Between 0.990 inches and 1.070 inches

Between 2.490 inches and 2.510 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5306-01-134-5706

Head Style:
Double hexagon w/hole
Head Height:
0.422 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Extended Washer Diameter:
0.562 inches
Extended Washer Thickness:
Between 0.090 inches and 0.100 inches
End Application:
Spec item
Thread Diameter:
0.375 inches
Grip Length:
Between 1.440 inches and 1.500 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Surface Finish:
63.0 microinches grip
Material:
Steel comp 8740
Material Specification:
Ams 6322 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Ams 2400 assn standard single treatment response

## NSN 5306-01-134-5706

Machine Bolt - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0