

View Online at <https://aerobasegroup.com/nsn/5306-01-134-5738>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.375 inches and 0.584 inches

Fastener Length:

Between 0.750 inches and 0.770 inches

Head Style:

Button

Head Diameter:

Between 0.782 inches and 0.844 inches

Head Height:

Between 0.188 inches and 0.208 inches

End Application:

Medium mine protected vehicle - mmpv

Neck Length:

Between 0.186 inches and 0.219 inches

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

60000 pounds per square inch

Neck Width:

Between 0.368 inches and 0.388 inches

Material:

Steel

Surface Treatment:

Cadmium and chromate or zinc and chromate

Surface Treatment Specification:

Qq-p-416 ty2 cl3 federal specification 1st treatment response or mil-c-81562 ty2 cl3 military specification 1st treatment response or qq-z-325 ty2 cl3 federal specification 2nd treatment response or mil-c-81562 ty2 cl3 military specification 2nd treatment response

Thread Series Designator:

Unc

Specification Or Standard:

4 grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-81562 spec.