

View Online at <https://aerobasegroup.com/nsn/5306-01-135-1138>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.100 inches and 0.180 inches

Fastener Length:

Between 0.470 inches and 0.500 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.218 inches and 0.226 inches

Head Height:

Between 0.134 inches and 0.138 inches

Hole Diameter:

Between 0.033 inches and 0.039 inches

First Diameter From Head:

Between 0.094 inches and 0.098 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.320 inches and 0.370 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.138 inches

Width Across Flats:

Between 0.1094 inches and 0.1111 inches

Hole Quantity:

2

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

80000 pounds per square inch

Hole Configuration Style:

Round internal hexagon

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

Material Specification:

66 federal standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0