## NSN 5306-01-135-1144

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-135-1144 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.374 inches and 0.441 inches **Fastener Length:** Between 1.072 inches and 1.119 inches **Head Style:** Double hexagon **Head Height:** Between 0.200 inches and 0.220 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Grip Diameter:** Between 0.3733 inches and 0.3742 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.678 inches and 0.698 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c **Surface Finish:** 32.0 microinches grip **Product Name:** Navy special project Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium or cadmium and chromate **Surface Treatment Specification:** Nas 672 assn standard 1st treatment response or mil-c-8837 type 2 class 2 military specification 2nd treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

## NSN 5306-01-135-1144

Shear Bolt - Page 2 of 2



	• -			
In	ıŧ	( )t	Measure	•

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.