

View Online at <https://aerobasegroup.com/nsn/5306-01-135-4135>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.444 inches and 0.497 inches

Fastener Length:

Between 1.141 inches and 1.171 inches

Head Style:

Spline extended washer

Head Height:

Between 0.194 inches and 0.234 inches

Extended Washer Diameter:

Between 0.460 inches and 0.470 inches

Extended Washer Thickness:

Between 0.026 inches and 0.046 inches

Grip Diameter:

Between 0.2485 inches and 0.2495 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.081 inches first hole

Head Minor Diameter:

Between 0.297 inches and 0.312 inches

Thread Diameter:

0.250 inches

Grip Length:

Between 0.677 inches and 0.697 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

220000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.949 inches first hole and 0.989 inches first hole

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0