

View Online at <https://aerobasegroup.com/nsn/5306-01-135-6717>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.657 inches

**Fastener Length:**

Between 2.173 inches and 2.203 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.327 inches and 0.347 inches

**Width Between Flats:**

Between 0.423 inches and 0.438 inches

**Extended Washer Diameter:**

Between 0.691 inches and 0.701 inches

**Extended Washer Thickness:**

Between 0.044 inches and 0.064 inches

**Shoulder Diameter:**

0.3740 inches first shoulder and 0.3745 inches first shoulder

**Shoulder Length:**

1.428 inches first shoulder and 1.448 inches first shoulder

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0