

View Online at <https://aerobasegroup.com/nsn/5306-01-136-4111>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.420 inches

Fastener Length:

3.190 inches

Head Style:

Double hexagon extended washer

Head Height:

0.265 inches

Width Between Flats:

0.250 inches

Extended Washer Diameter:

Between 0.292 inches and 0.313 inches

Extended Washer Thickness:

0.055 inches

Locking Feature:

Undercut grip

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Thread Diameter:

0.190 inches

Grip Length:

2.770 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Surface Finish:

32.0 microinches grip

Product Name:

Navy special project

Special Features:

Undercut head

Material:

Steel comp 4140 or steel comp 4340 or steel comp 6150 or steel comp 8740

Material Specification:

Mil-s-5626 military specification single material response or mil-s-5000 military specification single material response or mil-s-8503 military specification single material response or mil-s-6049 military specification single material response

Surface Treatment:

Oxide

Surface Treatment Specification:

Ams2485 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.