

View Online at <https://aerobasegroup.com/nsn/5306-01-136-4111>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.420 inches

**Fastener Length:**

3.190 inches

**Head Style:**

Double hexagon extended washer

**Head Height:**

0.265 inches

**Width Between Flats:**

0.250 inches

**Extended Washer Diameter:**

Between 0.292 inches and 0.313 inches

**Extended Washer Thickness:**

0.055 inches

**Locking Feature:**

Undercut grip

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Thread Diameter:**

0.190 inches

**Grip Length:**

2.770 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Surface Finish:**

32.0 microinches grip

**Product Name:**

Navy special project

**Special Features:**

Undercut head

**Material:**

Steel comp 4140 or steel comp 4340 or steel comp 6150 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification single material response or mil-s-5000 military specification single material response or mil-s-8503 military specification single material response or mil-s-6049 military specification single material response

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Ams2485 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.