## NSN 5306-01-136-5334

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-136-5334



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.291 inches and 0.341 inches

### Fastener Length:

Between 1.739 inches and 1.769 inches

#### Head Style:

Hexagon

Head Height:

Between 0.125 inches and 0.140 inches

#### Width Between Flats:

Between 0.430 inches and 0.439 inches

#### Grip Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

#### **Thread Diameter:**

0.250 inches

Grip Length:

Between 1.428 inches and 1.448 inches

#### Thready Qty Per Inch (tpi):

28

## Distance From Head Largest Bearing Surface To Shank Hole Center:

1.611 inches first hole and 1.661 inches first hole

## Surface Finish:

63.0 microinches grip

## Material:

Titanium alloy

## Material Specification:

Nas 621 assn standard single material response

## **Thread Series Designator:**

Unjf

## **Specification Data:**

80205-nas654 professional/industrial association standard

## Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5306-01-136-5334

Shear Bolt - Page 2 of 2

Fiig: A003b0

