

View Online at <https://aerobasegroup.com/nsn/5306-01-136-5746>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.523 inches and 0.563 inches

**Fastener Length:**

Between 2.471 inches and 2.491 inches

**Head Style:**

Spline drive shear head

**Head Height:**

Between 0.340 inches and 0.360 inches

**Width Between Flats:**

Between 0.970 inches and 0.978 inches

**Grip Diameter:**

Between 0.6235 inches and 0.6240 inches

**Thread Diameter:**

0.625 inches

**Grip Length:**

Between 1.928 inches and 1.948 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.346 inches all holes and 2.376 inches all holes

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0