

View Online at <https://aerobasegroup.com/nsn/5306-01-137-7040>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

1.750 inches

**Fastener Length:**

Between 4.400 inches and 4.600 inches

**Head Style:**

Button

**Head Diameter:**

Between 1.469 inches and 1.594 inches

**Head Height:**

Between 0.375 inches and 0.406 inches

**Neck Length:**

Between 0.375 inches and 0.406 inches

**Thread Diameter:**

0.750 inches

**Thready Qty Per Inch (tpi):**

10

**Min. Tensile Strength (psi):**

60000 pounds per square inch

**Neck Width:**

Between 0.741 inches and 0.768 inches

**Material:**

Steel comp 1108 or steel comp 1109 or steel comp 1110 or steel comp 1117 or steel comp 1118 or steel comp 1132 or steel comp 1137 or steel comp 1140 or steel comp 1141 or steel comp 1145 or steel comp 1146 or steel comp 1151

**Material Specification:**

Astm a307 assn standard all material responses

**Surface Treatment:**

Cadmium and chromate or zinc

**Surface Treatment Specification:**

Qq-p-416, type 2 class 3 federal specification 1st treatment response or mil-c-81562, type 2 class 3 military specification 1st treatment response or qq-z-325, type 2 class 3 federal specification 2nd treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

1 type and 1 class and a style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-81562 spec.