NSN 5306-01-138-5338

Assembled Washer Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-138-5338 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.400 inches and 0.450 inches **Fastener Length:** Between 0.785 inches and 0.815 inches **Head Style:** Hexagon **Head Height:** Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.430 inches and 0.439 inches Washer Quantity: **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Primary Washer Outside Diameter:** Between 0.495 inches and 0.520 inches **Primary Washer Style:** Flat **Primary Washer Material Thickness:** Between 0.028 inches and 0.036 inches **Special Features:** Washer anodizing or chemically treated per mil-c-5541 Material: Titanium alloy **Material Specification:** Ams 4967 6al-4v assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5306-01-138-5338

Assembled Washer Bolt - Page 2 of 2



Fiig:

A003b0