

View Online at <https://aerobasegroup.com/nsn/5306-01-138-5485>

Thread Direction:

Right-hand

Thread Length:

Between 0.990 inches and 1.070 inches

Fastener Length:

Between 1.365 inches and 1.385 inches

Head Height:

Between 0.412 inches and 0.432 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Extended Washer Diameter:

Between 0.552 inches and 0.572 inches

Extended Washer Thickness:

Between 0.090 inches and 0.100 inches

Hole Diameter:

Between 0.060 inches and 0.080 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 0.315 inches and 0.375 inches

Hole Quantity:

4

Hole Type:

Drilled

Features Provided:

Finished head

Nonstandard Thread Pitch Diameter:

+0.3420/+0.3449 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

130000 pounds per square inch

Hardness Rating:

24.0 rockwell c and 35.0 rockwell c

Minimum Yield Strength:

85000 pounds per square inch

Hole Configuration Style:

Double hexagon longitudinal hole

Surface Finish:

63.0 microinches grip

Material:

Iron alloy 660

Material Specification:

Ams 5732 assn standard single material response

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0