

View Online at <https://aerobasegroup.com/nsn/5306-01-140-3070>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.340 inches

**Fastener Length:**

1.715 inches

**Head Style:**

Spline drive shear head

**Head Height:**

0.210 inches

**Width Between Flats:**

Between 0.578 inches and 0.585 inches

**Hole Diameter:**

0.107 inches

**Grip Diameter:**

Between 0.3740 inches and 0.3745 inches

**Shank Unthreaded Hole Diameter:**

0.107 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

1.375 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hole Configuration Style:**

Round

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.586 inches first hole and 1.596 inches first hole

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0