

View Online at <https://aerobasegroup.com/nsn/5306-01-140-3070>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.340 inches

Fastener Length:

1.715 inches

Head Style:

Spline drive shear head

Head Height:

0.210 inches

Width Between Flats:

Between 0.578 inches and 0.585 inches

Hole Diameter:

0.107 inches

Grip Diameter:

Between 0.3740 inches and 0.3745 inches

Shank Unthreaded Hole Diameter:

0.107 inches first hole

Thread Diameter:

0.375 inches

Grip Length:

1.375 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

125000 pounds per square inch

Hole Configuration Style:

Round

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.586 inches first hole and 1.596 inches first hole

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0