

View Online at <https://aerobasegroup.com/nsn/5306-01-140-6355>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

1.000 inches

Fastener Length:

3.380 inches

Head Style:

Flat chamfer

Head Diameter:

Between 1.107 inches and 1.125 inches

Head Height:

Between 0.740 inches and 0.750 inches

First Diameter From Head:

0.600 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

2.380 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.750 inches

Width Across Flats:

0.625 inches

Thready Qty Per Inch (tpi):

10

Criticality Code Justification:

Zzzy

Externally Relieved Body Diameter Quantity:

1

Material:

Stainless steel

Surface Treatment:

Chromium threads

Special Test Features:

Special quality control testing

Surface Treatment Specification:

Mil-c-23422 military specification single treatment response threads

Test Data Document:

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Reference Number Differentiating Characteristics:

As differentiated by material which must conform to ships parts control center special quality control provisions and certified free from mercury contamination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-23422 spec.