Externally Relieved Body Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-141-0923

| Thread Cla  | 155.   |
|-------------|--|
| 3a          |  |
| Thread Di   |  |
| Right-hand  |  |
| Thread Le   | -  |
| 3.250 inch  |  |
| Fastener I  | .ength:  |
| 6.750 inch  | 25   |
| Head Style  | ::   |
| Hexagon     |  |
| Head Heig   | ht:  |
| 1.250 inch  | 3S   |
| Width Bet   | ween Flats:  |
| 3.125 inch  |  |
|             | eter From Head:  |
| 2.750 inch  | 3S   |
| Distance F  | rom Largest Bearing Surface Of Head To End Of First Diameter:  |
| 3.500 inch  | 2S   |
| End Appli   | cation:  |
| Propeller o | nboard 378 ft whec coast guard vessels   |
| Thread Dia  | ameter:  |
| 3.000 inch  | ese estatution esta |
| Thready C   | ty Per Inch (tpi):   |
| 20          |  |
| Min. Tensi  | le Strength (psi):   |
| 1240000 p   | ounds per square inch  |
| Minimum     | Yield Strength:  |
| 1040000 p   | ounds per square inch  |
| Externally  | Relieved Body Diameter Quantity:   |
| 1           |  |
| Material:   |  |
| Stainless s | teel   |
| Thread Se   | ries Designator:   |
| Un          |  |
| Shelf Life: |  |
| N/a         |  |
| Unit Of Me  | asure:   |
|             |  |
| Demilitaria | ation:   |
| No          |  |
| Fiig:       |  |
|             |  |