

View Online at <https://aerobasegroup.com/nsn/5306-01-141-2506>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.710 inches and 0.760 inches

Fastener Length:

Between 1.970 inches and 2.000 inches

Head Style:

Dished hexagon

Head Height:

Between 0.250 inches and 0.265 inches

Width Between Flats:

Between 0.741 inches and 0.752 inches

Shoulder Diameter:

0.5141 inches first shoulder and 0.5151 inches first shoulder

Shoulder Length:

1.240 inches first shoulder and 1.260 inches first shoulder

Thread Diameter:

0.500 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Shoulder Shape:

Round first shoulder

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas 2908 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0